


ET-971 Pinless Moisture Meter

FEATURES


- Pinless and non-invasive Measuring
- HD backlight screen for read easily
- Visual and audible alerts
- Pinless measurement depth around 30mm below the surface
- Detect ambient humidity and temperature value
 - With LED lighting, convenient for use in areas with insufficient light
- 9-grades of wood density
- Green-yellow-red LED light to indicate the moisture level



Three color LED Indicator light



LED lighting



Detect 30mm



9 Grades Of Wood Density

Specifications

Model	ET-971
Wood range	4%~80%
Wood accuracy	±2%(measured in an environment of 25°C/15%RH)
Resolving power	0.5%
Wood density selection	1~9
Digital updates	3 times/second
Over range display	When the value exceeds 80, over range prompt "OL"
Environmental temperature range	-20°C~60°C/-4°F~140°F
Accuracy	±1.0°C/1.8F
Resolving	0.1
Overload display	Display "LO" below range and "HI" above range
Humidity range	20~100%RH
Accuracy	35~75%RH; ±5%RH, other; ±7%RH
Resolving	1
Power supply	3*1.5V AA battery
Auto power off	Automatically shut down for 15 minutes without operation
Working temperature & humidity	-10°C~50°C/-4°F~140°F; 10~75%RH
Storage temperature & humidity	-20°C~60°C/-4°F~140°F; ≤85%RH
Dimensions(L*W*H)	225*68*29mm
Weight	230g